



CRANE PROJECT



RELIABLE
PARTNERS

MOVING
FORWARD

PT. OGB Environmental Technologies

Komplek Grand Kota Bintang Blok C1-C2 lantai 8,
Jl. KH. Noer Ali, Jakasampurna, Kalimantan, Bekasi Barat -17142.
+62 81 334 884 020
sales@ogbenvtech.com

OGB Engineering B.V

Welbergweg 74 7556 PE - Hengelo OV
Netherlands
+31 6 52 660099

Email:
info@ogbengineering.com
www.ogbenvtech.com/www.ogb-engineering.com

ogbenvtech.com

Subject to be changed without notice, no rights reserved. Technical features and drawings in this brochure are for illustrative purposes only.



STRAIGHT BOOM CRANE



▼SQS200-4




▼SQS350-4



▼SQS125-4


SQS 88-3

Item	Unit	SQS88-3
Max lifting moment	kN-m	88
Max lifting capacity	kg	3500
Max outreach	m	6.3
Max lifting height	m	7.8
Rated flow of hydraulic system	L/min	25
Oil tank capacity	L	60
Rated pressure of hydraulic system	MPa	18
Recommend power	kw	20
Installation space	mm	550
Stewing angle	°	360
Crane weight	kg	1000
Control type		Manual Operation




SQS 88-4

Item	Unit	SQS88-4
Max lifting moment	kN-m	88
Max lifting capacity	kg	3500
Max outreach	m	9.2
Max lifting height	m	10.5
Rated flow of hydraulic system	L/min	25
Oil tank capacity	L	60
Rated pressure of hydraulic system	MPa	18
Recommend power	kw	20
Installation space	mm	550
Stewing angle	°	360
Crane weight	kg	1050
Control type		Manual Operation




SQS 100-3

Item	Unit	SQS100-3
Max lifting moment	kN-m	100
Max lifting capacity	kg	4000
Max outreach	m	7.2
Max lifting height	m	8.8
Rated flow of hydraulic system	L/min	40
Oil tank capacity	L	60
Rated pressure of hydraulic system	MPa	18
Recommend power	kw	20
Installation space	mm	550
Stewing angle	°	360
Crane weight	kg	1050
Control type		Manual Operation




SQS 100-4

Item	Unit	SQS100-4
Max lifting moment	kN-m	100
Max lifting capacity	kg	4000
Max outreach	m	10.2
Max lifting height	m	11.5
Rated flow of hydraulic system	L/min	40
Oil tank capacity	L	60
Rated pressure of hydraulic system	MPa	18
Recommend power	kw	20
Installation space	mm	550
Stewing angle	°	360
Crane weight	kg	1120
Control type		Manual Operation




SQS 125-4

Item	Unit	SQS125-4
Max lifting moment	kN-m	125
Max lifting capacity	kg	5000
Max outreach	m	9.6
Max lifting height	m	11.5
Rated flow of hydraulic system	L/min	50
Oil tank capacity	L	60
Rated pressure of hydraulic system	MPa	20
Recommend power	kw	24
Installation space	mm	630
Stewing angle	°	360
Crane weight	kg	2300
Control type		Manual Operation



SQS 157-4

Item	Unit	SQS157-4
Max lifting moment	kN-m	157
Max lifting capacity	kg	6300
Max outreach	m	11.9
Max lifting height	m	13.8
Rated flow of hydraulic system	L/min	50
Oil tank capacity	L	90
Rated pressure of hydraulic system	MPa	23
Recommend power	kw	27
Installation space	mm	630
Stewing angle	°	360
Crane weight	kg	3300
Control type		Manual Operation



ogbenvtech.com

Subject to be changed without notice, no rights reserved. Technical features and drawings in this brochure are for illustrative purposes only.

