



CRANE PARTS



**PREMIUM
PRODUCTS**

**BEST
SERVICES**

PT. OGB Environmental Technologies

Komplek Grand Kota Bintang Blok C1-C2 lantai 8,
Jl. KH. Noer Ali, Jakasampurna, Kalimalang, Bekasi Barat-17142.
+62 81 334 884 020
sales@ogbenvtech.com

OGB Engineering B.V

Welbergweg 74 7556 PE - Hengelo OV
Netherlands
+31 6 52 660099
Email:

info@ogbengineering.com
www.ogbenvtech.com/www.ogbengineering.com

ogbenvtech.com


Subject to be changed without notice, no rights reserved. Technical features and drawings in this brochure are for illustrative purposes only.

KNUCKLE BOOM CRANE




SQZ 30

Item	Unit	SQZ30
Max lifting moment	kN-m	30
Max lifting capacity	kg	1800
Max outreach	m	4.4
Rated flow of hydraulic system	L/min	25
Oil tank capacity	L	40
Rated pressure of hydraulic system	MPa	18
Recommend power	kw	15
Installation space	mm	465
Slewing angle	°	270
Crane weight	kg	270
Outrigger span	mm	2780
Control type		Manual Operation




SQZ 80

Item	Unit	SQZ80
Max lifting moment	kN-m	80
Max lifting capacity	kg	4000
Max outreach	m	6.25
Rated flow of hydraulic system	L/min	20
Oil tank capacity	L	60
Rated pressure of hydraulic system	MPa	20
Recommend power	kw	15
Installation space	mm	715
Slewing angle	°	360
Crane weight	kg	1500
Outrigger span	mm	3457
Control type		Manual Operation




SQZ 100

Item	Unit	SQZ100
Max lifting moment	kN-m	100
Max lifting capacity	kg	5000
Max outreach	m	7.67
Rated flow of hydraulic system	L/min	50
Oil tank capacity	L	90
Rated pressure of hydraulic system	MPa	24
Recommend power	kw	20
Installation space	mm	740
Slewing angle	°	360
Crane weight	kg	2800
Outrigger span	mm	5010
Control type		Manual Operation




SQZ 126

Item	Unit	SQZ126
Max lifting moment	kN-m	126
Max lifting capacity	kg	6300
Max outreach	m	9.58
Rated flow of hydraulic system	L/min	50
Oil tank capacity	L	90
Rated pressure of hydraulic system	MPa	24
Recommend power	kw	20
Installation space	mm	740
Slewing angle	°	360
Crane weight	kg	3300
Outrigger span	mm	5010
Control type		Manual Operation




SQZ 160

Item	Unit	SQZ160
Max lifting moment	kN-m	160
Max lifting capacity	kg	8000
Max outreach	m	9.98
Rated flow of hydraulic system	L/min	45
Oil tank capacity	L	90
Rated pressure of hydraulic system	MPa	28
Recommend power	kw	20
Installation space	mm	1000
Slewing angle	°	360
Crane weight	kg	3200
Outrigger span	mm	5675
Control type		Elevated Seat



SQZ 200

Item	Unit	SQZ200
Max lifting moment	kN-m	200
Max lifting capacity	kg	10000
Max outreach	m	9.98
Rated flow of hydraulic system	L/min	45
Oil tank capacity	L	90
Rated pressure of hydraulic system	MPa	28
Recommend power	kw	20
Installation space	mm	1000
Slewing angle	°	360
Crane weight	kg	3400
Outrigger span	mm	5675
Control type		Elevated Seat



ogbenvtech.com


Subject to be changed without notice, no rights reserved. Technical features and drawings in this brochure are for illustrative purposes only.



Integrity | Reliability | Technology | Innovation


SQZ 240

Item	Unit	SQZ240
Max lifting moment	kN-m	240
Max lifting capacity	kg	12000
Max outreach	m	11.5
Rated flow of hydraulic system	L/min	60
Oil tank capacity	L	90
Rated pressure of hydraulic system	MPa	30
Recommend power	kw	20
Installation space	mm	1068
Slewing angle	°	360
Crane weight	kg	3600
Outrigger span	mm	5870
Control type		Elevated Seat




SQZ 600

Item	Unit	SQZ600
Max lifting moment	kN-m	600
Max lifting capacity	t/m	19.1/3
Max operating range	m	14.9
Telescopic Arm	m	7
Slewing angle	°	360
Rated pressure	MPa	30
Rated Oil Flow	L/m	80
Outrigger Span	mm	8200
Crane Deadweight	kg	6700
Installation space	mm	1460
Control type		Elevated Seat




SQZ 1280

Item	Unit	SQZ1280
Max lifting moment	kN-m	1280
Max lifting capacity	t/m	38.0/3
Max operating range	m	14.1
Telescopic Arm	m	7-9
Slewing angle	°	360
Rated pressure	MPa	30
Rated Oil Flow	L/m	100
Outrigger Span	mm	8200
Crane Deadweight	kg	11000
Installation space	mm	2650
Control type		Elevated Seat




SQZ 5200

Item	Unit	SQZ5200
Max lifting moment	kN-m	5200
Max lifting capacity	t/m	130/4
Max operating range	m	15.23
Telescopic Arm	m	7-9
Slewing angle	°	360
Rated pressure	MPa	30
Rated Oil Flow	L/m	108
Outrigger Span	mm	7950
Crane Deadweight	kg	30000
Installation space	mm	3880
Control type		Elevated Seat




SQZ 330

Item	Unit	SQZ330
Max lifting moment	kN-m	330
Max lifting capacity	kg	16500
Max outreach	m	13.7
Rated flow of hydraulic system	L/min	60
Oil tank capacity	L	90
Rated pressure of hydraulic system	MPa	30
Recommend power	kw	20
Installation space	mm	1307
Slewing angle	°	360
Crane weight	kg	5200
Outrigger span	mm	5855
Control type		Elevated Seat




SQZ 700

Item	Unit	SQZ700
Max lifting moment	kN-m	700
Max lifting capacity	t/m	24.8/3
Max operating range	m	15.5
Telescopic Arm	m	7-9
Slewing angle	°	360
Rated pressure	MPa	30
Rated Oil Flow	L/m	80
Outrigger Span	mm	8200
Crane Deadweight	kg	7300
Installation space	mm	1508
Control type		Elevated Seat




SQZ 2180

Item	Unit	SQZ2180
Max lifting moment	kN-m	2180
Max lifting capacity	t/m	55/4
Max operating range	m	14
Telescopic Arm	m	7-9
Slewing angle	°	360
Rated pressure	MPa	30
Rated Oil Flow	L/m	108
Outrigger Span	mm	8300
Crane Deadweight	kg	19000
Installation space	mm	2820
Control type		Elevated Seat




SQZ 6000

Item	Unit	SQZ6000
Max lifting moment	kN-m	6000
Max lifting capacity	t/m	150/4
Max operating range	m	14.2
Telescopic Arm	m	7-9
Slewing angle	°	360
Rated pressure	MPa	30
Rated Oil Flow	L/m	108
Outrigger Span	mm	7950
Crane Deadweight	kg	31000
Installation space	mm	2750
Control type		Elevated Seat




SQZ 400

Item	Unit	SQZ400
Max lifting moment	kN-m	400
Max lifting capacity	kg	20000
Max outreach	m	15.9
Rated flow of hydraulic system	L/min	80
Oil tank capacity	L	90
Rated pressure of hydraulic system	MPa	30
Recommend power	kw	20
Installation space	mm	1494
Slewing angle	°	360
Crane weight	kg	6200
Outrigger span	mm	8011
Control type		Elevated Seat




SQZ 800

Item	Unit	SQZ800
Max lifting moment	kN-m	800
Max lifting capacity	t/m	26.0/3
Max operating range	m	14.42
Telescopic Arm	m	7
Slewing angle	°	360
Rated pressure	MPa	30
Rated Oil Flow	L/m	80
Outrigger Span	mm	8200
Crane Deadweight	kg	7900
Installation space	mm	1380
Control type		Elevated Seat



SQZ 3300

Item	Unit	SQZ3300
Max lifting moment	kN-m	3300
Max lifting capacity	t/m	83/4
Max operating range	m	17.06
Telescopic Arm	m	7-9
Slewing angle	°	360
Rated pressure	MPa	30
Rated Oil Flow	L/m	108
Outrigger Span	mm	8300
Crane Deadweight	kg	23000
Installation space	mm	3450
Control type		Elevated Seat



◀ KNUCKLE BOOM CRANE TRUCK SERIES ▶



SQZ126



SQZ160



SQZ240



SQZ500



SQZ2600




SQZ700



SQZ5200


SQZ 500

Item	Unit	SQZ500
Max lifting moment	kN-m	500
Max lifting capacity	t/m	17.5/3
Max operating range	m	14.5
Telescopic Arm	m	7
Slewing angle	°	360
Rated pressure	MPa	30
Rated Oil Flow	L/m	80
Outrigger Span	mm	8200
Crane Deadweight	kg	5800
Installation space	mm	1450
Control type		Elevated Seat



SQZ 900

Item	Unit	SQZ900
Max lifting moment	kN-m	900
Max lifting capacity	t/m	29.3/3
Max operating range	m	15.64
Telescopic Arm	m	7-9
Slewing angle	°	360
Rated pressure	MPa	30
Rated Oil Flow	L/m	80
Outrigger Span	mm	8200
Crane Deadweight	kg	8900
Installation space	mm	1450
Control type		Elevated Seat



SQZ 4000

Item	Unit	SQZ4000
Max lifting moment	kN-m	4000
Max lifting capacity	t/m	100/4
Max operating range	m	14.84
Telescopic Arm	m	7-9
Slewing angle	°	360
Rated pressure	MPa	30
Rated Oil Flow	L/m	108
Outrigger Span	mm	8310
Crane Deadweight	kg	27000
Installation space	mm	3620
Control type		Elevated Seat

